RDM SPLITTER 6

The RDM/DMX Splitter 6 is a 6 port, rack mounting RDM "transparent" splitter designed for distribution of DMX-512A(RDM) signals in a lighting network. Easy to use with high quality XLR 5 pin signal connectors, this unit provides robust plug and play capabilities for the distribution of DMX within typical entertainment environments.

The RDM Splitter 6 provides six buffered, opto-isolated outputs for connection to and control of DMX and RDM capable devices. Packaged into a 1U high rack mounting package it allows the splitter a to become a key part of your lighting installation. Power to the unit is provided via a locking PowerCon connector, ensuring power cannot accidentally be disconnected, helping you to safeguard your data distribution network against accidental power disconnection.

- Compatible with both DMX-512A(RDM) and DMX 512(1990)
- 1U rack mount housing design
- Signal In/Thru (XLR 5pin) front or rear
- 6 ports optically isolated and buffered output (XLR 5 pin)
- CE / ETL/cETL and FCC marked
- Locking power connector with PowerCon power input







Specifications

Due to continuous improvements and innovations, specifications may change without notice.

Electrical

Supply Voltage	100-230 VAC
Frequency	50/60Hz
Power Consumption (max)	5 W

Connections

Input	2x XLR 5-pin (1 front and 1 rear)
Thru	2x XLR 5-pin (1 front and 1 rear)
Output	6x XLR 5-pin front
Power Input	1x PowerCon

Certification and Safety


Compliance CE / E	ETL/cETL and FCC marked
-------------------	-------------------------

Physical

0-40°C (32-104°F)
5-95% non-condensing
482.60 x 155 x 44 mm (18.9 x 6.1 x 1.75 in)
Black Die-cast aluminium
Desktop or 19" rack mount
1U
IP20
2.2 kg (4.85 lb)

RDM Splitter 6 Data Sheet

Dimensions



RDM Splitter 6 Data Sheet 3

Product and Accessories

Product Name Order Code

RDM Splitter 6, 1U Rack Mount 65026



Vari-Lite