

One of the most difficult speaker requirements to satisfy is a cost-effective mid-size speaker system that offers high quality sound no matter what the application. TOA HS-Series speakers are equipped with narrow-directivity control (90° horizontal × 40° vertical). This useful feature allows tailoring the speaker's dispersion characteristics to better suit the acoustic environment in which it is installed. The versatile HS-Series is compatible for use with 100V/70V lines for distributed applications. The HS-Series speakers are exceptional in offering useful features at an attractive price.



Order no: HS-1500WT

Specifications

| | |
|--------------------------------------|--|
| Frequency response | 60 Hz - 20 kHz |
| Connection | Neutrik NL4MP Speakon and M4 screw terminal, distance between barriers: 9 mm |
| Sensitivity (1#W, 1#m) (combined) | 98 dB |
| Speaker component | 38 cm cone-type, balanced dome-type x 6 |
| Rated input | 60 W |
| Tappings | 8 Ohm, 100 V line: 170 Ohm (60 W), 330 Ohm (30 W), 670 Ohm (15 W), 70 V line: 83 Ohm (60 W), 170 Ohm (30 W), 330 Ohm (15 W), 670 Ohm (7.5 W) |
| Rated impedance | 8 Ω, 100 V |
| Power handling capacity | Continuous pink noise: 100 W Continuous program: 300 W |
| Dimensions (W x H x D) | 451 x 560 x 400 mm |
| Dimensions (ø x D) | x 400 mm |
| Finish | Polypropylene resin, off-white (RAL 9010 or equivalent) |
| Operating temperature | -10 °C to +50 °C |

Appearance

