

DESONO™ KUBO3

FULL RANGE 3-INCH SURFACE MOUNT LOUDSPEAKER



FEATURES

- Zoom Certified
- High speech intelligibility coupled with full-range music reproduction
- Stylish yet subtle design; blends well in many environments
- Can be mounted to track lighting rails through innovative optional accessories
- IP40 rated
- Magnetically attached end caps hide audio connections and bracket hardware
- Loudspeaker overload protection for 24/7 failsafe operation

APPLICATIONS

Retail Outlets · Bars and Restaurants · Hotels · Cafés and Bistros · Kiosks · Corporate Meeting Rooms · Sound Masking

DESCRIPTION

The Desono KUBO3 full-range 3" surface mount loudspeaker is the result of increasing demand for more stylish yet subtle audio products. Designed to blend into any background, the KUBO3 delivers crystal clear sound for all your background music needs, while the bass reflex port provides a fast and dynamic bass response.

Available in black or white, the 140° range of motion allows the KUBO3 to be installed on walls or ceilings in either horizontal or vertical orientation. The audio connections and bracket hardware are hidden under magnetically attached end caps, providing a refined look for high visibility locations. For retail applications, optional accessories are available that allow the KUBO3 to be attached directly to many types of track lighting rails.

The Desono KUBO3 is an excellent choice for indoor audio applications that demand superior speech intelligibility and full range music reproduction, as well as open deck sound masking applications.

TECHNICAL SPECIFICATIONS

Operating Mode	Passive	
Operating Environment	Indoor	
Operating Range (-10dB)	115 Hz to 20 kHz	
Nominal Beamwidth (H x V)	100° x 100°	
Transducers	1 x 3" (76 mm) polypropylene cone	
Continuous Power Handling @ Nominal Impedance	14V	25W @ 8Ω (100W peak)
Nominal Sensitivity @ 1m	@ 1W 84 dB	@ 2.83V 84 dB
Nominal Maximum SPL @ 1m	Peak 104 dB	Continuous 98 dB
Protection	3-step self-resetting protection	
Recommended Amplifiers	25W - 50W @ 8Ω (14V - 20V)	

PHYSICAL

Input Connection	(2x) 2-way Euroblock connectors for daisy-chaining; connectors accept up to 12 AWG (2.5 mm ²) conductors
Mounting Provisions	U-bracket
Environmental	IP40 per IEC 60529
Dimensions H x W x D	4.9" x 5.2" x 4.3" (125 mm x 131 mm x 109 mm)
Weight	2.1 lbs (1 kg)
Finish	Refer to the Technical Drawings (page 3)
Accessories (included)	U-bracket; safety cable

OPTIONS


Accessories	LRABAS(-BL/-W): Basic light rail adaptor, black or white LRAPRE(-BL/-W): Premium light rail adaptor, black or white
-------------	--

Biamp strives to improve its products on a continual basis. Specifications are therefore subject to change without notice. Data presented on this spec sheet represents the basic performance specifications for the model. For a detailed analysis of this loudspeaker's performance, please download the GLL file from our website: biamp.com


DESONO KUBO3

FULL RANGE 3-INCH
SURFACE MOUNT LOUDSPEAKER


FREQUENCY RESPONSE (dB SPL)




HORIZONTAL OFF-AXIS RESPONSE (dB)




IMPEDANCE (Ohms)



VERTICAL OFF-AXIS DOWN RESPONSE (dB)



BEAMWIDTH (Degrees)



DESONO KUBO3

FULL RANGE 3-INCH SURFACE MOUNT LOUDSPEAKER

TECHNICAL DRAWING / DIMENSIONS / FINISH

H x W x D
4.9" x 5.2" x 4.3"
(125 mm x 131 mm x 109 mm)

Unit Weight
2.1 lbs (1 kg)

Shipping Weight
3.1 lbs (1.4 kg)

Grille:
Steel
White (RAL 9016) or Black (RAL 9011) finish

Enclosure / Finish
ABS plastic, matte finish, White or Black

