

N-8020MS

MASTER STATION

This Master Station is designed to connect to the IP Intercom Exchange, and provides hands-free or handset conversation of high sound quality. It features dustproof and waterproof construction, and can be used in locations exposed to ambient temperatures ranging from -10 °C to +50 °C. In addition to the functions of the standard Master Station, the Industrial-Use Station permits connection of external speakers, and can take out control signal for dial-in indicator from its contact output. This station can be mounted to the wall using an optional YC-280 wall mounting bracket.



Article number: N-8020MS Y
Alternative products: N-8065MS, N-8010MS,
N-8000MS, N-8011MS, N-8031MS,
N-8033MS

Specifications

Power source	48 V DC (supplied from the IP network intercom exchange)
Frequency response	300 Hz - 7 kHz
Power consumption	2.4 W (max.)
Outputs	Open collector output (The contacts have polarity.) / Withstand voltage: max. 30 V DC, Control current: max. 50 mA, screwless connector (2P)
Wiring method	1 set of twisted pair cable
Transmission range	Max. 1500 m (ø 0.65 mm, Loop resistance < 170 Ω) / 2,900 m (ø 0.9 mm)
Speech method	Hands-free or handset conversation
External speaker connector	0.6 W, 8 Ω, screwless connector (2P)
Dimensions (W x H x D)	170 x 220 x 97,8 mm
Dimensions (ø x D)	x 97,8 mm
Finish	ABS resin, grey,

N-8020MS

MASTER STATION

Appearance

