

DATA SHEET

PARLÉ™ CBC 2500 PM CEILING MOUNTED CONFERENCE AUDIO BAR



The Parlé™ CBC 2500 PM is a ceiling mounted, all-in-one conferencing bar for collaboration spaces where wall mounting might be difficult. Featuring a sleek design that hangs from any open plan ceiling with an aesthetically pleasing pole mount assembly, the CBC 2500 PM is quickly and cleanly installed with a single mounting point.

With integrated Acoustic Echo Cancellation (AEC) and AI Noise Reduction, the CBC 2500 PM uses a 27-element mic array and Biamp Beamtracking™ technology to actively track and intelligently mix conversations from around the room. Two smart speakers use distortion compensation and dynamic bass enhancement technology to create room filling audio with superior speech reproduction.

The CBC 2500 PM also features Biamp Launch, an automated tuning system that optimizes the audio to each unique conferencing space.

FEATURES

- Beamtracking technology actively tracks and intelligently mixes conversations
- AI noise reduction algorithm for clear voice reproduction
- Low distortion smart speakers
- Biamp Launch for one touch automatic tuning
- LED indications for mute status
- Pole mount assembly included
- Certified for Microsoft Teams and Zoom

ARCHITECTS & ENGINEERS SPECIFICATION

The conferencing audio bar shall be designed to work with soft codec conferencing systems. The conferencing audio bar shall include a twenty-seven element digital microphone array. The conferencing audio bar microphones shall offer multidirectional beamforming and automatic signal tracking capabilities. The Beamtracking technology shall operate in conjunction with acoustic echo cancellation technology (AEC) in accordance with US Patent 9659576. The conferencing audio bar shall have two low distortion speakers. The conferencing audio bar shall include dynamic bass enhancement and distortion compensation technology. The conferencing audio bar shall support an automated audio setup process that optimizes audio output levels after physical installation is complete. The conferencing audio bar shall be mountable in an open ceiling application. The conferencing audio bar shall be CE marked, UL listed, and compliant with the RoHS directive. Warranty shall be three years. The conferencing audio bar shall be the Parlé™ CBC 2500 PM.

PARLÉ ABC 2500 SPECIFICATIONS

MICROPHONES		Interfaces	
Microphone Technology:	27-Element Digital Array	USB 3.0:	1x Type C
Frequency Response (100 Hz - 8 kHz):	-10dB	Power Sources	
Polar Pattern:	Active Beamformed	USB-C:	60W
Pickup Range (25dBA noise floor):	> 23 feet (7 m)	External Power Supply:	100-240VAC 50/60Hz (12VDC, 4.74A)
SNR (@ 1kHz, 94dB SPL, A-Weighted):	69 dB	Overall Dimensions	
Maximum SPL (@ 1kHz, THD < 10%):	130 dB	Height:	3.9 inches (100 mm)
Indicators:	Mute Indicator (Green/Red/Off LEDs)	Width:	37 inches (940 mm)
Sensitivity (@ 1Pa):	> -37dBFS ± 1dB	Depth:	2.5 inches (64 mm)
Microphone Data Rate Output:	48 kHz	Weight:	9.6 lbs (4.4 kg)
Audio Processing:	AEC (Acoustic Echo Cancellation)	Environmental	
Noise Reduction:	AI filter	Operating Temperature:	32 - 104° F (0 - 40° C)
LOUDSPEAKERS		Humidity:	0-90% (non-condensing)
Frequency Response (57 Hz - 20 kHz):	-10 dB	Altitude:	0-10,000 ft (0-3000m) MSL
Nominal Beamwidth (H x V):	180° x 180°	Compliance:	
Transducers:	2x 2.5 in (60 mm) full range	FCC Part 15B (USA)	
Rated Maximum SPL (@ 1m):	90 dB (continuous) 96 dB (peak)	CE Marked (Europe)	
Sensitivity (@ 1m, 2.83V):	84 dB	UL and C-UL listed (USA and Canada)	
THD (@ 1kHz):	< 0.2%	RoHS Directive (Europe)	
Nominal Impedance:	4Ω		
Continuous Rated Power			
(6 dB crest factor, HPF @ 60 Hz):	20W		
Sampling Rate:	48 kHz		

PARLÉ CBC 2500 PM COVERAGE AREA BY MOUNTING HEIGHT

Mounting Height (AFF)	Coverage Width	Coverage Length	Coverage Area
8' (2.4M)	11' (3.4M)	17' (5.2M)	187 sq ft (17.4M²)
9' (2.7M)	11' (3.4M)	17' (5.2M)	187 sq ft (17.4M²)
10' (3.0M)	10' (3.0M)	16' (4.9M)	160 sq ft (14.9M²)
11' (3.4M)	9' (2.7M)	15' (4.6M)	135 sq ft (12.5M²)
12' (3.7M)	8' (2.4M)	14' (4.3M)	112 sq ft (10.4M²)

PARLÉ CBC 2500 PM SPECIFICATIONS

Bundle Contents:	(1) Parlé ABC 2500/2500a Bar
	(1) Pole mount assembly
	(1) Bar mounting plate
	Pipe (3 lengths) [6", 1', 2' (153, 305, 610 mm)]
	(1) Bracket coupler and nut
	(1) USB cable 10m (32.8')
	(1) Power cable 10m (32.8')
	(4) Lag bolts
	(1) Instructions

Biamp strives to improve its products on a continual basis. Specifications are therefore subject to change without notice.

Biamp, Devio, and Parlé are either trademarks or registered trademarks of Biamp Systems, LLC in the United States and other countries. Other product names referenced may be trademarks or registered marks of their respective owners and Biamp Systems is not affiliated with or sponsored by these companies.