

SBC-AX

Axient Charging Module

The Shure Axient charging module for rechargeable batteries, SBC-AX, user guide. Version: 2 (2020-G)

Table of Contents

	Installation		3
SBC-AXAxient Charging Module	3		
	Included Cor	mponents	3
SBC-AX Charging Modules	3		
	Specification	ns	3
WARNING	3		
	Certifications	s	4

SBC-AX Axient Charging Module

SBC-AX Charging Modules

These charging modules allow SB900 batteries to be used with AXT900, AXT903, and AXT904 battery chargers.

WARNING

- Battery packs may explode or release toxic materials. Risk of fire or burns. Do not open, crush, modify, disassemble, heat above 140°F (60°C), or incinerate.
- · Follow instructions from manufacturer
- · Only use Shure charger to recharge Shure rechargeable batteries
- · WARNING: Danger of explosion if battery incorrectly replaced. Replace only with same or equivalent type.
- · Never put batteries in mouth. If swallowed, contact your physician or local poison control center
- · Do not short circuit; may cause burns or catch fire
- Do not charge or use battery packs other than Shure rechargeable batteries
- · Dispose of battery packs properly. Check with local vendor for proper disposal of used battery packs.
- · Batteries (battery pack or batteries installed) shall not be exposed to excessive heat such as sunshine, fire or the like
- · Do not immerse the battery in liquid such as water, beverages, or other fluids.
- Do not attach or insert battery with polarity reversed.
- · Keep away from small children.
- · Do not use abnormal batteries.
- Pack the battery securely for transport.

Installation

Charging modules may be installed interchangeably into the charger.

Caution! Remove power and batteries when installing charging modules.

- To remove a module, remove the four (4) mounting screws and pull.
- · To install, slide the module into the housing (noting the orientation of the guide rails) until it is flush with the housing.
- · Replace the screws.

Included Components

Mounting Screws (8) for Charger Modules (30B13476)

Specifications

```
Charge Current
750 mA

Dimensions
44 x 86 x 100 mm (1.8 x 3.4 x 4.0 in.), H x W x D

Weight
119 g (4.2 oz.)

Housing
Molded ABS, Cast aluminum
```

Certifications

Meets essential requirements of the following European Directives:

- WEEE Directive 2012/19/EU, as amended by 2008/34/EC
- RoHS Directive EU 2015/863

Note: Please follow your regional recycling scheme for batteries and electronic waste