

SUB 15-AX PROFESSIONAL ACTIVE 15" SUBWOOFER

			-
RCF	9696969696969 9696969696969		


Description The SUB 15-AX is a portable 15" high-power active subwoofer for live sound applications with fully featured processing, a color touch panel, and remote control via Bluetooth[®]. The combination of a latest-generation transducer with a powerful Class-D amplifier delivers sound pressure levels up to 133 dB with exceptional clarity and headroom. SUB AX subwoofers are designed specifically for small to mid-sized venues and ideal for portable applications. SUB 15-AX is the ideal complement for 10" or 12" woofer-size loudspeakers; it centralizes speaker management inside the subwoofer, providing dual crossovers, 8-band EQs, routing, delays, cardioid configurations, and recallable crossover presets. The polyurea-coated all-wood cabinet features a sealed Powercon True1 Top connector.

Features	 > 2200 Watt Class-D Amplifier > 133 dB MAX SPL > 15" Woofer, bass reflex housing > Digital Crossover w/ Presets > Multi-ply hardwood polyurea-coa > LiveRemote App > Dual XLR/TRS combo Input + Lin > Bass Motion Control excursion m > Powercon True1 Top Sealed AC C 	ık, Dual XLR Xover Out anagement		
Part Number	13000832 SUB 15-AX	100-120 V	Black	EAN 8024530021849
	13000835 SUB 15-AX	220-240 V	Black	EAN 8024530021818
	13000877 SUB 15-AX W	100-120 V	White	EAN 8024530021894
	13000878 SUB 15-AX W	220-240 V	White	EAN 8024530022044




SUB 15-AX PROFESSIONAL ACTIVE 15" SUBWOOFER

Line Art 2D



TECHNICAL SPECIFICATIONS



Acoustical	specifications

Acoustical specifications	Frequency Response Max SPL @ 1m	35 Hz ÷ 120 Hz 133 dB			
Transducers	Woofer	1 x 15", 3.0" v.c			
Input/Output section	Input signal Input connectors Output connectors Input sensitivity	bal/unbal Combo XLR/Jack XLR -2 dBu/+4 dBu			
Processor section	Protections Limiter Controls	Thermal Soft Limiter Encoder for Volume control and data entry. Touch Screen for parameter management and monitor.			
Power section	Total Power Cooling Connections	2200 W Peak, 1100 W RMS Convection Powercon TRUE1 TOP IN/OUT			
Standard compliance	Safety agency	CE compliant			
Physical specifications Size / Weight	Cabinet/Case Material Handles Pole mount/Cap Grille Color Height	M20 thread Steel Black, White	1 handle per side M20 thread Steel		
	Width Depth Weight	420 mm / 16.54 590 mm / 23.23	420 mm / 16.54 inches 590 mm / 23.23 inches 51.4 kg / 69.23 lbs		
Rigging / Mounting	POLE MOUNT KITS 13360638 PM-KIT M20 13360067 PM-KIT M20	White Black	EAN 8024530022303 EAN 8024530014599		



SUB 15-AX PROFESSIONAL ACTIVE 15" SUBWOOFER

Protections |

BAGS, COVERS 13360529 CVR 004

Black

EAN 8024530020415